

URETHANE BONDED PISTON

GPM International Triplex Urethane Bonded Piston is designed to perform in the regular drilling conditions, with following features.

Features:

- Designed for High Temperature and Pressure Service (170 °F/ 5000 psi)
- Suitable for oil based mud
- Excellent chemical and abrasion resistance in the most demanding well conditions
- Water based mud version can be special requested
- Reduced operating costs in challenging operating environments



Description	Size	Part Number
Urethane Bonded Piston	4"	LLU-40-B15
Urethane Bonded Piston	4-1/2"	LLU-44-B15
Urethane Bonded Piston	5"	LLU-50-B15
Urethane Bonded Piston	5-1/2"	LLU-54-B15
Urethane Bonded Piston	6"	LLU-60-B15
Urethane Bonded Piston	6-1/4"	LLU-62-L15
Urethane Bonded Piston	6-1/2"	LLU-64-L15
Urethane Bonded Piston	6-3/4"	LLU-66-L15
Urethane Bonded Piston	7"	LLU-70-L15
Urethane Bonded Piston	8"	LLU-80-L15

GPM International is a supplier of durable oilfield replacement parts for a wide variety of drilling mud pumps. Inventory products including mud pump fluid end parts, handling tool, etc. All of our products are fully exchangeable with O.E.M. standards.