

HIGH TEMPERATURE URETHANE BONDED PISTON

GPM International Triplex High Temperature Urethane Bonded Piston is designed to perform in the harshest of drilling conditions, with following features.

Features:

! Designed for High Temperature and Pressure Service

(250°F/ 7500psi)

! Suitable for oil, synthetic or water based mud

! excellent chemical and abrasion resistance in the most demanding well conditions

! Enhanced piston running life with a proprietary blend of lubricating agents

! Reduced operating costs in challenging operating environments



Description	Size	Part Number
HT Urethane Bonded Piston	4"	LLU-40-B15-HT
HT Urethane Bonded Piston	4-1/2"	LLU-44-B15-HT
HT Urethane Bonded Piston	5"	LLU-50-B15-HT
HT Urethane Bonded Piston	5-1/2"	LLU-54-B15-HT
HT Urethane Bonded Piston	6"	LLU-60-B15-HT
HT Urethane Bonded Piston	6-1/4"	LLU-62-L15-HT
HT Urethane Bonded Piston	6-1/2"	LLU-64-L15-HT
HT Urethane Bonded Piston	6-3/4"	LLU-66-L15-HT
HT Urethane Bonded Piston	7"	LLU-70-L15-HT

GPM International is a supplier of durable oilfield replacement parts for a wide variety of drilling mud pumps. Inventory products including mud pump fluid end parts, handling tool, etc. All of our products are fully exchangeable with O.E.M. standards.